



4833 Saratoga Blvd # 138
Corpus Christi, TX 78414

Direct: 361-906-0863 Toll Free: 866-556-6324
Fax: 361-906-0824

Recommended for Use On Flexi Tile

Cleaner *Pledge Multi Surface Floor Cleaner.* Follow directions on bottle. If applying Armstrong Shine Keeper, rinse floor with warm clean water and let completely dry before applying sealer.

Purple Power Industrial Strength Cleaner and Degreaser

Spray on Surface, let set for several minutes but do not let it dry on surface. Wipe with clean cloth. After rinse with clear water.

- Use plenty of clean rags, when cloth appears dirty turn over. dirt on cloth will smear dirt around and not clean properly.

Clear Sealer *Armstrong Shine Keeper For No Wax Vinyl and Linoleum*

Follow directions on bottle. After floor is clean or on new floor apply one light coat for gloss and protective seal. To seal seam apply to more generous coats being sure that each coat is dry before applying another coat

Adhesive *Para bond - Solvent Free Acrylic Wall Base Adhesive*

Apply adhesive with a 1/16th notch trowel. Knock down the adhesive with the smooth side of the trowel picking or spreading any excess. Let stand 15 to 20 minutes before applying tile.

Adhesive Henry 430 – Premium Commercial Tile VCT Adhesive

Apply adhesive using thinnest trowel available. Wait 30-90 minutes until adhesive is dry to touch (tacky but no transfer to fingers) Install tile. Do not wet tile for 5 days after installation.