



# PLEASE READ CAUTIONS

1. In rare instances some rubber products may stain the tile's surface. Test by placing a single tile under rubber tires, chair bottoms, coasters etc. for 48 hours prior to installation.
2. Check all cartons to ensure they are the same batch code. Color variations may occur between batches.
3. Most chemicals will not stain. Pet urine will cause tile to yellow. Remove chemical spills as soon as possible. Petroleum product may cause tile to deteriorate if left unattended.
4. To insure easy installation, remove the tiles from the cartons and spread them out on the floor where they can acclimate to room temperature 24 hours prior to installation.
5. Tile will need to slide across subfloor as it expands, if laying tile on a rough surfaces like plywood or rough concrete an underlayment of .03 mm (or thicker) plastic will allow the tile to slide as it expands.
6. Be sure to leave a 1/4" expansion gap around all edges in wall-to-wall installations.
7. Any non-slip vinyl wax or sealer will add to the ease of cleaning. Perfection Floor Tile recommends Armstrong Shine Keeper.
8. This Tile is for Interior Use Only.

## Perfection Floor Tile: Flexi-Tile LIFETIME RESIDENTIAL WARRANTY

Your purchase of the world's finest floating residential vinyl floor comes with the following warranty. It is written to validate your decision to choose Flexi-Tile Floor Tiles from the many choices available. This Warranty will provide a lifetime of peace of mind and the confidence that your new floor will provide years of outstanding service. "Lifetime" is defined as the length of time the original purchaser of the floor resides in the dwelling where the floor is installed. "Residential" is defined as private single family dwelling or residence, not used for commercial purposes.

### Perfection Floor Tile guarantees that:

1. The wear layer on this floor will not wear through from foot traffic.
2. The wear layer will not discolor from normal household spills.
3. The tile will not promote the growth of mildew from top or bottom.
4. The tile will be unaffected by moisture in the subfloor.
5. The tile will lay flat without bucking or warping under normal household conditions.

If you have a warranty question or claim, please contact Perfection Floor Tile at [sales@reflexmouldingsusa.com](mailto:sales@reflexmouldingsusa.com) or call 877-363-7831

### Exclusions and fine print:

1. The tiles must be visually inspected prior to installation. If a defect is detected, please contact the manufacturer at the address below.
2. All installation instructions must be followed as detailed on the installation instruction sheet.
3. Damage caused by natural disasters, including but not limited to earthquakes, hurricanes, etc. is not covered by this warranty.
4. We will not reimburse labor cost for initial installation or reinstallation if the installation was done by the home owner or unlicensed contractor.
5. We will reimburse labor cost for a defective floor if installed by a licensed contractor and homeowner can provide bona fide cost documentation.
6. All reimbursements are subject to prior approval by Reflex Moulding's U.S.A.'s management and verification of purchase, physical inspection of the floor by our representative, and/or digital pictures submitted by the purchaser.